

KX15DTAM



Premium, Grade 3 protection Deliver optimum detection with patented anti-masking

Ideal internal detection for every room! Fit the wired Grade 3 KX15DTAM and the user can rest assured that they have superior detection for their property.

Complies with EN50131-1

KX15DTAM



Ultimate reliability with Dual Technology (DT)

Consisting of both a Passive Infrared (PIR) and microwave sensor in one housing, both sensors need to be activated simultaneously to get an alarm condition. This increases stability and makes the KX15DTAM ready to detect in even the harshest environments.

Adaptable, optimised & stylish

• Volumetric detection

Ideal large area coverage for living rooms, dining rooms, kitchens and more.

• 15m detection coverage

Detection coverage up to 15m.

• ABS plastics

3mm polished finish produces a professional and sleek finish while reducing electrostatic interference on the PIR sensor.

• Sealed optics

Protect the detector from possible insect infestation, shields air movement in front of the pyro-electric sensor and protects against adverse reflections from inside the detector housing.

• Triple LED indication

The KX15DTAM indicates the detection technologies as they detect, with orange indicating 'microwave', green indicating 'PIR' and blue indicating an alarm activation.

Avoid false alarms with Blue Wave Technology (BWT)

Advanced signal processing and 3D optics safeguard against false alarms and improve immunity to interference:

• Digital temperature compensation

Digitally adjusts the sensitivity of the detector to maintain its specified range when the background temperature is close to body temperature.

• Automatic sensitivity

The detector self-adapts to changing environmental conditions to maintain stability and intruder catch performance.

• Independent Floating Thresholds (IFT)

Eliminates electrical environmental disturbances by ensuring alarm thresholds are always kept within predetermined limits.

• Optical 3D system

Improves the detection of moving targets, ensures more precise signals can be received from the PIR and allows protection of the area below the detector (creep zone).

• Different microwave frequencies

Avoids interference (cross-talk) that can occur when two detectors with microwave modules in them are installed within close proximity of each other. This optimises detector stability.

Arming safely & beat the burglar with Anti-Interference Technology

• Anti-Masking

This Grade 3 technology provides superior protection against any attempts to mask any of the three technologies within the detector with a variety of materials, such as: cardboard, duct tape, sprays, lacquers or aluminium foil.

| | |
|----------|----------|
| Partcode | KX15DTAM |
|----------|----------|

Optical & Range Features

| | |
|-------------------------------------|-----------|
| Adjustable Anti-asking (Anti-spray) | ✓ |
| Volumetric coverage | ✓ |
| Curtain coverage | ✓ |
| Long range coverage | ✓ |
| Maximum range | 15m / 18m |
| Optimal installation height | 1.8-2.4m |
| Creep-zone protection | ✓ |

Technical Characteristics

| | |
|---|---|
| Animal Immune | × |
| Blue Wave Technology | ✓ |
| Automatic sensitivity | ✓ |
| Digital temperature compensation | ✓ |
| Anti-cloaking technology AND/OR | ✓ |
| Separate indication: Microwave, PIR and Alarm | ✓ |
| 3 microwave frequencies to avoid interference | ✓ |
| EOL resistors on board | ✓ |
| Tamper protection included | ✓ |

Accessories

| | |
|--|---|
| Wall/Ceiling brackets included (KXBRACKET-C, KXBRACKET-W) | ✓ |
| Long range and curtain lenses included (KX30-LR e KX18-LC) | ✓ |
| Anti-tamper kit included (KX-TAMPER) | ✓ |

Certification & Warranty

| | |
|---|------------|
| Electrical conformity | CE |
| EN50131 | Grade 3 |
| Environmental class | II |
|  | CA12.01176 |
| Warranty | 5 years |

• Anti-Blocking

This Grade 4 technology prevents the system from being armed if there is anything blocking the field of view of any of the sensors within the detector. This would then need to be removed before the system will arm.

• Anti-Cloaking

This changes the method of activating a DT detector; either triggering both PIR and microwave technologies or activating either technology individually to activate an alarm condition.

Beat the burglar with tamper proof brackets

Supplied with tamper proof brackets to ensure that maximum security is maintained against accidental or malicious tampering of the system.

Faster & more efficient wiring with selectable EOL resistors

The KX15DTAM incorporates various EOL tamper and alarm resistor values to cater for DEOL wiring for most control panels on the market.