


DS-PK1-E-WE Wireless Keypad

The DS-PK1-E-WE series wireless keypad can connect to AX PRO for alarm control and operation. It can also notice alarm by indicator and buzzer.



Features

- 868 MHz two-way wireless communication
- AES-128 encryption
- Stay/away arming, disarming, alarm clearing for specified area or all areas
- LED indicates the programmed area
- One-Push fire alarm, panic alarm, and medical alarm. Silent/Audible alarm selectable. etc.
- Output control
- Full touch key design with LED backlight
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Easy replaceable battery
- Frequency hopping against jamming for reliable transmission

Available Models

DS-PK1-E-WE

Specifications

| Model | | DS-PK1-E-WE |
|------------------------|-----------------------|--|
| RF | Frequency | 868 MHz |
| | Modulation | 2GFSK |
| | Distance | 1200m (open area) |
| Interface & component | Tamper switch | Supported, front and rear panel tamper-proof |
| | Power switch | Power on/off |
| | Buzzer | Supported |
| | Indicator | 4: fault (orange), enrollment/signal (red/green), arm(blue), disarm(green) and alarm (red) |
| | Backlight | white |
| | Key | Number key: 0 to 9 Function key: *, #, stay arming, away arming, disarming, and output |
| Application & protocol | Protocol | Tri-X, two-way communication |
| Electrical & battery | Power Consumption | Quiescent current: 180 uA Max current: 251mA Voltage: 1.5 VDC |
| | Battery type | Four AA batteries |
| | Battery life span | Standby time more than two years |
| Others | Operation humidity | 10% to 90% (No condensing) |
| | Operation temperature | -10 °C to +55 °C (-4 °F to +122 °F) |
| | Color | White |
| | Installation | Screw mounting |
| | Dimension (W x H x D) | 140 (5.50") x 86 (3.38") x 22 (0.87") mm |
| | Weight | Without batteries: 151 g (5.33 oz), and 23 g (0.81 oz)each battery |