


DS-PDEB2-EG2-WE
Wireless Emergency Button
 Quick Start Guide

EN 50131-1:2006+A1: 2009+A2:2017
 EN 50131-3:2009
 EN 50131-5-3:2017
 Security Grade(SG) I 2
 Environmental Class(EC) II
 Certified by Telefication



ENGLISH

1 APPEARANCE

1. Indicator 2. Button 3. Tamper Button 4. Battery

2 ENROLLMENT

3 INSTALLATION

I. Check signal strength.
 II. Align the groove to install the detector.
 a. with screw b. with sponge tape

Note: Non EN compliant after Installation wit Sponge Tape.

4 TEST 1.Button Activated 2.Alarm Received

5 REPLACE BATTERY

User Manual

Scan the QR code for more information and operation help.

Specification

LED indicator	Blue (alarm)
LED alarm confirmation	Flashing LED
Tamper protection	Front & Back
Operating temperature	-10 °C to 55 °C (14 °F to 131 °F) -10 °C to 40 °C (14 °F to 104 °F) Certified
Storage temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operating humidity	10% to 90%
Dimension (W × H × D)	63.8mm × 63.8mm × 17.9mm
Weight	45.5g
Transmission frequency	868MHz
RF range	1.2Km (open area)
Battery	CR2450 x 1 (included) 620mAh capacity
Standard battery life	5 years
PS type	Type C
Low voltage level	2.60 V
Consumption	Quiescent Current: 23.02uA Max: 36.89mA
Classification	Use inside the supervised premises

1

User Manual

2

3

4

5