

DS-PDEBP2-EG2-WE

Wireless Portable Emergency Button

- Accidental press protection
- Fully remote configurable through App
- IP54 daily environment protection
- Frequency hopping against jamming for reliable transmission
- Optional lanyard and wristband accessory available

▪ Specification

Model		DS-PDEBP2-EG2-WE
Feature	Button	2
	Tamper Protection	None
	Signal Strength Indicator	Support
Interface	LED Indicator	Red / Green
Transmission	Transmission Technology	Tri-X Wireless
	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	868MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	1Km
	Frequency Hopping	Support
	Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	Standard Battery Life	3 years in work status (being triggered 20 times per day)
	Power Supply	Battery Powered
	Battery Type	CR2035 x 1
	Typical Voltage	3V
General	Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%
	IP Rate	IP54
	Dimension(WxHxD)	φ38 × 12mm
	Weight	13.5g
	Application Scenario	Portable

▪ Available Model

DS-PDEBP2-EG2-WE

▪ Accessory

▪ Optional

