

DS-7700NXI-I4/S AcuSense Series NVR

Key Feature

- H.265+/H.265/H.264+/H.264 video formats
- Intelligent analytics based on deep learning algorithm
- Up to 4-ch perimeter protection
- Up to 1-ch facial recognition for video stream, or up to 4-ch facial recognition for face picture
- Up to 16/32-ch IP camera inputs
- Up to 16-ch 1080p decoding capability
- Up to 160/256 Mbps incoming bandwidth



Compression and Recording

- H.265+ compression effectively reduces the storage space by up to 75%
- Full channel IP cameras connection
- Adopt stream over TLS encryption technology which provides more secure stream transmission service
- Support double verification for playback and downloading

HD Video Output

- Provide independent HDMI and VGA outputs
- HDMI video output at up to 4K resolution

Storage and Playback

- Up to 4 SATA interfaces for HDD connection
- 16-ch synchronous playback at up to 1080p resolution

Smart & POS Function

- Support multiple VCA (Video Content Analytics) events
- Smart search for the selected area in the video, and smart playback to improve the playback efficiency
- POS information overlay on live view and playback
- POS triggered recording and alarm


Network & Ethernet Access

- 2 self-adaptive 10/100/1000 Mbps Ethernet interfaces
- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management
- Smooth streaming technology
- Support web access without plug-in

Typical Application


Facial Recognition and Face Picture Comparison

Modeling and analyzing face pictures captured by cameras. Realize blacklist alarm and stranger alarm via face picture library. Search target people by picture and name features.



Perimeter Protection

Adopt deep learning algorithm to reduce false alarm, effectively reduces the false alarm caused by tree branches, leaves, shadow, light, vehicles, small animals, etc.




Specification

Model	DS-7716NXI-I4/S	DS-7732NXI-I4/S
Facial Recognition¹		
Facial detection and analytics	Face picture comparison, human face capture, face picture search	
Face picture library	Up to 16 face picture libraries, with up to 10,000 face pictures in total (each picture ≤ 512 KB, total capacity ≤ 150 MB)	
Face picture comparison	4-ch face picture comparison alarm	
Performance of facial detection and analytics	1-ch human face capture (HD network camera, up to 4 MP, H.264/H.265)	
Perimeter Protection¹		
False alarm reduction	Up to 4-ch 2 MP (H.264/H.265) video analysis for human and vehicle recognition to reduce false alarm; Up to 12 rules in total	
Video and Audio		
IP video input	16-ch	32-ch
	Up to 12 MP resolution *: 32 MP and 24 MP is only available for channel 1 when ultra HD resolution mode is enabled.	
Incoming bandwidth	160 Mbps	256 Mbps
Outgoing bandwidth	256 Mbps	256 Mbps
HDMI1 output	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI1/VGA simultaneous output	
HDMI2 output	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI2/VGA independent output	
VGA output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI1/VGA simultaneous output	
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480	
Audio output	1-ch, RCA (Linear, 1 KΩ)	
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)	
Decoding		
Decoding format	H.265+/H.265/H.264+/H.264/MPEG4	
Recording resolution	32 MP/24 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF *: 32 MP and 24 MP is only available for channel 1 when ultra HD resolution mode is enabled.	
Playback mode	Normal/Smart, Event, Tag, Eternal File	
Synchronous playback	16-ch	
Live view window division	1/2/4/6/8/9/16	1/2/4/6/8/9/16/25/32/36
Aux port window division	1/2/4/6/8/9/16	1/2/4/6/8/9/16/25/32/36
Capability	16-ch @ 1080p (30 fps)	
Dual stream recording	Support	
Stream type	Video, Video & Audio	

Audio compression	G.711ulaw/G.711alaw/G.722/G.726/MP2L2
Network	
Remote connections	128
Network protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
Network interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Auxiliary interface	
Serial port	RS-485 (half-duplex), RS-232, Keyboard
SATA	4 SATA interfaces supporting hot-plug
Capacity	Up to 10 TB capacity for each disk
eSATA	1 eSATA interface
Alarm in/out	16/4
USB interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0
General	
Power supply	100 to 240 VAC, 50 to 60 Hz
Total power	≤ 80 W
Consumption (without HDD)	≤ 30 W
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	10% to 90%
Chassis	19-inch rack-mounted 1.5U chassis
Dimension (W × D × H)	445 × 400 × 75 mm (17.5" × 15.7" × 3.0")
Weight (without HDD)	≤ 5.6 kg (12.3 lb)
Certification	
FCC	Part 15 Subpart B, ANSI C63.4-2014
CE	EN 55032:2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4


1: Facial recognition and perimeter protection cannot be enabled at the same time. Enable one function will make the other one unavailable.

Dimension



Unit: mm

Physical Interface



No.	Description	No.	Description
1	eSATA interface	9	USB 3.0 interface
2	Audio input	10	VGA output
3	Video output	11	RS-485 serial interface
4	RS-232 serial interface	12	Keyboard interface
5	100 to 240 VAC power supply	13	Controller Port, Alarm In/Alarm Out
6	Network interfaces	14	GND
7	Audio output	15	Power Switch
8	HDMI output		