

DS-PK1-LT-WE Wireless Keypad



- 868MHz two-way wireless communication
- LCD screen and LED to indicate system status
- System configuration through LCD screen
- Multiple operations like stay/away arm, disarm, silent alarm, output control
- One-Push fire alarm, panic alarm, and medical alarm
- Full touch key design with LED backlight
- Fully remote configurable through App

▪ Specification

Hardware features	
Tag reader built in	Supported
Serial port	3
Tamper-Proof	Supported, front and rear
Buzzer	Supported
Power switch	Power on/off
Electrical characteristics	
Battery type	Four CR123 batteries
Operation humidity	10% to 90%
Operation temperature	-10 °C to 55 °C
Battery life span	Standby time more than two years
Power consumption	Quiescent current: 80 uA Max current: 300 mA Voltage: 3 V
Wireless transmission	
RF frequency	868 MHz
RF modulation	2GFSK
RF distance	1200 m (open area)
Wireless technology	Tri-X Wireless Technology
Display	
Numeric key	Number key: 0 to 9 Function key: *, #, Query, Away arm, Stay arm, Disarm, Output, Project, Right, Left
LED indicator	Fault(orange), Enrollment/Signal (red/green), Arm(blue), Disarm(green), Alarm (red)
General	
Installation method	Wall mounting
Dimension(W×H×D)	174.63 mm × 109.62 mm × 25.25 mm
Weight	With batteries: 348 g Without batteries: 282 g
Color	White

▪ Available Model

DS-PK1-LT-WE

