

## DS-K1T502DBFWX-C Video Access Control Terminal



- Manage access control, video intercoms, and video security with one device
- IP65 & IK09 protections, as well as increased stability with zinc alloy materials
- Multiple authentication methods, including fingerprint, card, etc.
- Remote control via the Hik-Connect mobile app
- Connects to external access controller via Wiegand protocol
- Two-way audio via SIP 2.0 protocol
- RS-485 communication for connecting external card reader

## ▪ Specification

<b>System</b>	
Operating system	Linux
<b>Video</b>	
Lens	1
Resolution	2 MP
FOV	HFOV = 110°; VFOV = 81°; DFOV = 122°
Video standard	PAL (Default) and NTSC
<b>Network</b>	
Wired network	10 M/100 M self-adaptive
Wi-Fi	Support
Bluetooth	Support
<b>Interface</b>	
Network interface	1
Lock control	1
Exit button	1
Door contact input	1
Alarm input	1
Alarm output	1
TAMPER	1
RS-485	1
Wiegand	1 (Output only)
SD Card Slot	1
<b>Capacity</b>	
Fingerprint capacity	10,000
Card capacity	100,000
Event capacity	300,000
<b>Authentication</b>	
Fingerprint module	Capacitive fingerprint recognition
Card type	Mifare 1 card, DESfire card
Card reading distance	0 ~ 3 cm
<b>Function</b>	
Two-way audio	Support
Hik-Connect	Support
<b>General</b>	
Power supply	1 A (DC 12 V ~ DC 24 V)
Power consumption	≤12 W
Working temperature	-40 °C ~ +70 °C (-40 °F ~ +158 °F)
Protective level	IK09, IP65
Language	Arabic, English, French, Indonesian, Italian, Portuguese (Brazil), Russian, Spanish (Europe), Thai, Ukrainian, Vietnamese

## ▪ Available Model

DS-K1T502DBFWX-C

▪ Dimension



