

DS-UC4 2K Web Camera





- High quality imaging with 2560 × 1440 resolution
- Low distortion lens for reducing image distortion
- Built-in dual-microphone with clear sound
- USB Type-C interface, supporting USB 2.0 protocols
- Plug-and-play, no need to install driver software
- Support auto focus



Specification

Camera	
Image Sensor	4 MP CMOS
Signal System	PAL/NTSC
Frame Rate	MJPG:
	2560 × 1440 @ 30 fps/25 fps
	1920 × 1080 @ 60 fps/50 fps/30 fps/25 fps
	1280 × 960 @ 60 fps/50 fps/30 fps/25 fps
	1280 × 720 @ 60 fps/50 fps/30 fps/25 fps
	640 × 480 @ 60 fps/50 fps/30 fps/25 fps
	640 × 360 @ 30 fps/25 fps
	YUV2:
	1920 × 1080 @ 5 fps
	1280 × 960 @ 5 fps
	1280 × 720 @ 10 fps
	640 × 480 @ 30 fps
	640 × 360 @ 30 fps
Resolution	2560 (H) × 1440 (V)
Min. Illumination	0.1 Lux @ (F1.2, AGC ON)
Shutter Time	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s
Lens	3.6 mm fixed focal lens
Field of View	horizontal FOV: 80°, vertical FOV: 50°, diagonal FOV: 88°
Lens Mount	M8
Day & Night	24/7 Color Imaging
Angle Adjustment	pan: 0° to 360°; tilt: 0° to 90°; rotation: 0°
	*It is recommended to use a self-prepared tripod when the tilt angle is larger than 35°.
Digital Zoom	1.5 ×
Cable Length	2 m
Depth of Field	0.1 m to ∞
Image	
Wide Dynamic Range (WDR)	Digital WDR
White Balance	Auto
Audio	
Audio Sampling Rate	16 kHz
Interface	
Video Output	USB 2.0
Operating System	Recommended systems
	Windows 7/8/10/11 (resolution higher than 1080P is only available in Windows 8.1
	and above version)
	Android 8.1 and above version
	Linux 4.14 and above version
	macOS 10.12 and above version
	Chrome OS
Built-in Microphone	2 built-in microphones, picking up sounds in the radius up to 5 meters
Indicator	White: Normally Working



General	
Operating Conditions	-10°C to 40°C (-40°F to 104°F), Humidity: 90% or less (non-condensing)
Power Supply	DC 5V ± 5% (USB)
Consumption	2.5 W MAX
Dimension	120 mm × 27.9 mm × 25.6 mm (4.72" × 1.10" × 1.01")
Weight	Approx. 147 g (0.32 lb.)
Accessory	
Packing List	Camera × 1
	USB Cable × 1
	Quick Start Guide × 1

Available Model

DS-UC4

Dimension





