

DS-3WF02C-5AC/O
Wireless Bridge

The wireless bridge can be applied in industries, such as wireless video security, railway, transportation, power and other industries, wireless video/data transmission, wireless coverage, carrier wireless backbone network construction, Wi-Fi wireless coverage, rural information construction, and wireless network coverage. The long-distance transmission of the device can guarantee multi-channel HD video transmission.


- All gigabit LAN ports
- TDMA supported
- Quick match through DIP switch
- Visualized topology management
- Up to 5 km wireless transmission distance

▪ Specification

Model		DS-3WF02C-5AC/O
Wireless Parameter	Max. Transmission Rate of Air Interface	≤ 867 Mbps
	Wireless Standard	IEEE 802.11/a/n/ac
	Working Frequency Band	5150 to 5250 MHz 5250 to 5350 MHz (DFS) 5470 to 5725 MHz (DFS) 5725 to 5850 MHz (Note: Available channel may vary with local regulations.)
	Transmitting Power	22 dBm (Note: Transmitting power may vary with local regulations.)
	Receiving Sensitivity	-58 ± 2 dBm@AC80 -MCS9; -84 ± 2 dBm@AC80 -MCS0
	Antenna Gain	12 dBi
	Antenna Angle	Beamwidth [3 dB] (35°± 5°)
	Network Parameters	Networking Mode
Hardware Parameter	Port Numbers	2 × Gigabit RJ45 ports
	LED Indicator	Power indicator, LAN indicator, signal intensity indicator
	Reset	Hardware resetting button
	Power Supply	12 VDC/1 A Passive PoE; 12 VDC, 1 A
Software Function	Application Function	TDMA, DFS, TPC, IFM, IPM
	Channel Width	20/40/80 MHz
	Channel Selection	Auto/manual selection
	Network Protocol	NTP (network time synchronization), SADP (auto search for IP address), HTTPS (web management), SSH (debugging)
	Security Mode	WPA2-PSK
	Security Mechanism	Wireless network name hidden
	Management Method	Web, HCP
	Upgrade	Web, iVMS-4200
General	System Log	Syslog, control center information
	Product Dimensions (W × H × D)	92 mm × 187 mm × 58 mm (3.62" × 7.36" × 2.28")
	Package Dimensions (W × H × D)	132 mm × 228 mm × 91 mm (5.19" × 8.97" × 3.58")
	Net Weight	0.307 kg (0.677 lb)
	Gross Weight	0.807 kg (1.779 lb)
	Packing List	Wireless bridge × 1, power adapter (12 VDC, 1 A) × 1, 1000 MB PoE injector × 1, binding tape × 2, quick start guide × 1
	Packing Method	Single unit packing
	Working Temperature	-30 °C to 70 °C (-22 °F to 158 °F)
	Working Humidity	5% to 95% (no condensation)
Storage Temperature	-40 °C to 85 °C (-40 °F to 185 °F)	


	Storage Humidity	5% to 95% (no condensation)
	Installation Mode	Pole mounting
	Power Consumption	2.65 W for typical (1-ch 2MP IPC), Max. 4.5 W
Approval	EMC	CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020); IC (ICES-003: Issue 7:2020); RCM (AS/NZS CISPR 32: 2015)
	Safety	UL (UL 60950-1); CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition); CE-LVD (EN 62368-1: 2014+A11: 2017)
	Chemistry	CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No.1907/2006)
	Radio	EN 301 893; EN 300 440; EN 62311; EN 301 489-3; EN 301 489-17; FCC Part 15.247;

▪ Typical Application



▪ Physical Interface

Interface/Button	Description
CPE/AP DIP Switch	Switch up or down to set the device as AP or CPE.
SSID	4-character SSID to realize 16 kinds of matching ways by switching up or down. The CPE will connect to the AP when its SSID matches the AP's.
PoE/LAN1	The 10/100/1000 Mbps adaptive RJ45 port, also can be used as a PoE port.
LAN2	The 10/100/1000 Mbps adaptive RJ45 port.
Reset	Long press for 4 sec to restore to factory settings.
DC 12V	If the PoE injector is not used for powering on the device, you can use the attached power adapter to connect the device to socket.



▪ Available Model

DS-3WF02C-5AC/O

DS-3WF02C-5AC/OV2

▪ Dimension

