

DS-PDP18-HM-WE Wireless Double PIR Detector

Wireless Double PIR Detector is a two-way wireless outdoor double PIR detector with up to 20000 lux high light resistance. This device is designed to protect the outdoor areas of your property and triggers an alarm before an intruder breaks in.

- High/Low mount adjustment
- IP65 weather resistance for outdoor application
- Multiple enrollment methods and easy installation
- Frequency hopping against jamming for reliable transmission



Specification

| Detection Performance | |
|-----------------------------------|------------------------------------|
| Detection Method | Passive infrared |
| Sensor Model | SFG323-711 |
| Detection Range | 18 m |
| Detection Angle | 90° |
| Detection Zones | 118 |
| Detectable Speed | 0.3 to 2m/s |
| Sensitivity | Auto,Pet |
| White Light Filter | 20000lux |
| Pet Immunity | Up to 24 kg |
| Digital Temperature | Support |
| Compensation | Support |
| Feature | |
| Digital Processing | Support |
| Sealed Optics | Support |
| Tamper Protection | Front, rear |
| Environment Temperature | Support |
| Indicator | |
| Signal Strength Indicator | Support |
| Interface | |
| Power Switch | Power up enrolling |
| LED Indicator | Blue (alarm) |
| Transmission | |
| Transmission Technology | Tri-X Wireless |
| Transmission Method | Two-Way RF Wireless |
| Transmission Frequency | 868 MHz |
| Transmission Security | AES-128 Encryption |
| Transmission Range(Free Space) | 1.6 km |
| Frequency Hopping | Support |
| Enrolling Method | Power up, Remote ID, QR Code |
| Electrical Characteristics | |
| Standard Battery Life | Up to 5 years (standby time) |
| Power Supply | Battery powered |
| Battery Type | CR123A × 2 |
| Typical Voltage | 3V |
| General | |
| Operation Temperature | -25 °C to 60 °C (-13 °F to 140 °F) |
| Storage Temperature | -25 °C to 60 °C (-13 °F to 140 °F) |
| Operation Humidity | 10% to 90% |
| IP Rate | IP65 |
| Dimension(WxHxD) | 67.3 mm × 141.6 mm × 60 mm |
| Weight | 301 g |
| Mounting Height | 2.5 m to 3 m high mount. |
| | 0.8 m to 1.2 m low mount |



| Mounting Method | Wall |
|----------------------|-----------------------------|
| Application Scenario | Indoor, outdoor |
| Bracket | Adjustment bracket included |

Available Model

DS-PDP18-HM-WE

Accessory

Optional



