

DH-PFS3008-8ET

8-Port Unmanaged Ethernet Switch



- · Supports eight 10/100 Mbps adaptive ports.
- Small and light, it is easy to carry and has multiple chips embedded in it.
- · Easy to operate.









System Overview

The Device is a layer-2 commercial switch. It has a high-performance switching engine and a large buffer memory to ensure smooth video stream transmission. With a full-metal and fanless design, the Device features great heat dissipation capability on the shell surface. The Device is an unmanaged switch, so it does not need to be configured through web interface, which simplifies installation.

Functions

Robust Design

Built to last, the architecture of the switch makes it highly reliable, operating with high-efficiency non-stop.

Plug and Play

Hassle-free, it does not require any configuration. Simply use after it is powered on.

Optimized Performance

All ports can transmit streams at high speeds without delay.

Easy Installation

Both desktop and wall mount installation are supported, making it suitable for a wide variety of scenarios.

Scene



Home



Shop







Meeting Room

Specification Hardware Included Power Adapter Yes 8 **Ethernet Port Ethernet Port Speed** 100 Mbps Description of Function Port 1–8: 8 × 10/100 Base-T Slots 5 VDC; 1 A **Power Supply** Operating Temperature 0 °C to +45 °C (+32 °F to +113 °F) Operating Humidity 5%-95% (RH) -40 °C to +70 °C (-40 °F to +158 °F) Storage Temperature 5%-95% (RH) Storage Humidity Idling: 0.1 W; **Power Consumption** Full load: 0.75 W Performance MTBF 929.51 years **Switching Capacity** 1.6 Gbit Packet Forwarding Rate 1.1904 Mpps 768 kbit Packet Buffer Size 2K MAC Table Size General Air discharge: 8 kV Contact discharge: 4 kV **Statics Protection Lighting Protection** Common mode: 2 kV Net Weight 0.23 kg (0.51 lb) Gross Weight 0.35 kg (0.77 lb) 133.5 mm \times 56.0 mm \times 22.0 mm **Product Dimensions** (5.26" × 2.20" × 0.87") 136.0 mm × 55.0 mm × 153.0 mm **Packaging Dimensions** (5.35" × 2.17" × 6.02") Casing Material Metal Installation Desktop mount

CE; FCC

Certifications

Dimensions (mm[inch])





