

DHI-ARC3800H-FW2(868)

Dahua Wireless Alarm Hub 2



Series Overview

The Alarm Hub manages the wireless alarm devices in your system to alert you when doors are broken into, windows are opened, glass breaks, fires break out and water leaks. If an intruder breaks in, the hub notifies the alarm receiving center and the mobile app (DMSS or DoLynk Care), and sends videos from the PIR Camera and IPC so that you can stay up to date on events, without the hassle of personally monitoring your scene.

Technical Specification

Port		
Wireless Zone	150 channels wireless peripherals (6 sirens, 64 PIR cameras, 64 keyfobs, 8 keypads and 4 repeaters)	
Network Mode	Supports installation of dual SIM cards. Only one card can be enabled at a time. Also, multiple frequency bands are supported for the SIM cards (GSM: 900/1, 800 MHz, WCDMA: B1/B8, LTE-FDD: B1/B3/B7/B8/B20/B28A, LTE- TDD:B38/B40/B41).	
Network Port	1 RJ-45, 10 Mbps/100 Mbps Ethernet port.	
Storage Battery	One built-in 4,750 mah rechargeable lithium battery.	
Video & Audio		
Video Input	8-ch IPC, which only supports the upload of alarm videos.	
Audio Output	1 channel	
Volume Control	Yes	
Voice Broadcast	Telephone and local speaker	

- Supports alarm video verification through integration of the IPC with the hub.
- Images can be remotely and quickly transferred from the PIR-Cam to the device.
- · Features voice call alarm.
- Supports wired and AP network configuration methods, which makes it easier to add the hub to apps and to switch to the hub's network.
- Supports multi-network redundancy for Ethernet, Wi-Fi and 4G networks to ensure the network remains stable and reliable.
- Supports two-way communication and frequency hopping to make communication with wireless peripherals stable and reliable.
- Features cloud update. You can also remotely update the device and wireless peripherals on the mobile app.
- Offers a dual backup system, and uses auto recovery when an update fails.

Function

1

F

Indicator Light	The indicator indicates the status of alarms, arming and	
Indicator Light	disarming, the network connection and device failure.	
Button	Includes a reset button, voltage button and AP switch button.	
SMS	Yes (up to 5 phone numbers)	
Phone Call	Yes (up to 5 phone numbers)	
Video Linkage	Yes	
Offline Cache	Stores up to 50 alarm messages.	
Arm and Disarm	App, keyboard, remote control, card, scheduled arming and disarming.	
Remote Update	Cloud update	
Low Battery Detection	Yes	
Tamper	Yes	
User Management	Functions can be shared by the app users. These include 1 installer, 1 administrator and 31 general users.	
Logs	Up to 5, 000 entries	
Transmission Protocol	SIA, SoftGuard	
Wireless		
Carrier Frequency	868.0–868.6 MHz	
Communication Mechanism	Two-way	




Alarm Hub | DHI-ARC3800H-FW2(868)


Communication Distance	Up to 2,000 m (6,561.68 ft) in an open space.	
Encryption Mode	AES128	
Frequency Hopping	Yes	
Wi-Fi	2.4 G	
General		
Language	Up to 7 languages are supported for SMS: English, Spanish (Latin America), French, Italian, Arabic, Turkish, and Danish. It is set as English by default. The alarm voice message feature and local speaker only support English.	
Power Supply	100–240 VAC, 50/60 Hz	
Standby Time	The battery lasts up to 12 hours when it is fully charged and is within the following conditions: It is connected to the Wi-Fi, its ID is connected to the alarm receiving center, the heartbeat interval is 1,800 seconds, and it is connected to 8 peripherals and the cloud.	
Power Consumption	≤12 W	
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)	
Operating Humidity	10%–90% (RH)	
Product Dimensions	174.8 mm × 174.8 mm × 38.3 mm (6.88" × 6.88" × 1.51") (L × W × H)	
Net Weight	510 g (1.12 lb)	
Gross Weight	860 g (1.90 lb)	
Installation	Supports wall mount and desktop mount installation.	
Casing Material	PC + ABS	
Certifications	CE	
Anti-corrosion Level	Basic Protection	
Storage Temperature	-10 °C to +55 °C (+14 °F to +131 °F)	
Storage Humidity	10%–90% (RH)	
Packaging Dimensions	254 mm × 211 mm × 61 mm (10.00" × 8.31" × 2.40") (L × W × H), standalone in the inner box 524 mm × 508 mm × 442 mm (20.63" × 20.00" × 17.40") (L × W × H), protective case	

Ordering Information			
Туре	Part Number	Description	
Alarm Hub	DHI-ARC3800H-FW2(868)	Dahua Wireless Alarm Hub 2	

Installation




Dimensions (mm[inch])



Application





Rev 002.000 ©2023 Dahua. All rights reserved. Design and specifications are subject to change without notice Pictures in the document are for reference only, and the actual product shall prevail.