

81mm

319mm








## Installation example:





## **DESTINATION**

Enclosure protects recorder against unauthorized access or theft (two keys included). Made of 1,2 mm steel plate. Set includes one key (different code), two keys included and tamper switch unwanted enclosure opening.

Due to vertical installation and low depth, it is ideal for places where deeper enclosures or cabinets type RACK 19" cannot be installed. After opening enclosure, front cover is held in a horizontal position, providing easy access to buttons on front panel of DVR. Enclosure has a special holder with retaining straps that allows for installation of recorders of following dimensions:

Width up to 260 mm, height: up to 55 mm, depth up to 250 mm.

## **TECHNICAL DATA:**

External dimensions of enclosure:	W=319, H=429, D + D <sub>2</sub> =81+14 [mm, +/-2]
External dimensions of front panel:	W,=325, H,=435 [mm, +/-2]
Dimensions of recorder compartment:	W <sub>1</sub> =260, H <sub>1</sub> =250, D <sub>1</sub> =55 [mm, +/-2]
Net/gross weight:	4,98 / 5,21 [kg]
Operating conditions:	Temperature: -10°C ÷ +40°C relative humidity 20%90%, without condensation
Material:	sheet metal, thickness: 1.2mm, anticorrosion protection, color RAL 9003 (white)
Destination:	inside
Tamper switch protection:	1 x microswitch: enclosure opening 0,5 A; 50 V DC max. NC – normally closed contacts Optionally: 1 x microswitch: detachment form wall, 0,5A; 50 V DC (required PKAZ067)
Closing:	lock MR008 (different code) x 1 pcs.
Notes:	distance from wall (mounting surface) – 14 mm set includes one key (different code), two keys included
Warranty:	2 years from production date