

Superior StreetSiren Plus G3 Jeweller

Wireless siren with advanced sabotage protection and an extended list of compliance certificates. For outdoor and indoor use.




3
GRADE
EN 50131

IK08

IP54




This is a device of the Superior product line. Only accredited Ajax Systems partners can sell, install, and maintain Superior products.



One device, multiple missions

- An audible alarm to deter intruders and attract attention
- Security state indication to inform users of the system being armed/disarmed
- LED and sound indication of entry/exit delays
- Chime feature to alert users to opening detectors being triggered while the system is disarmed
- After-alarm LED indication to show users and passing patrols if there were any alarms in the system




Superior Jeweller communication technology

- Up to 3,500 m (11,450 ft) of radio communication² in open space
- Enhanced data encryption
- Regular polling to display current device states
- Device authentication to prevent spoofing




Sabotage resistance

- Tamper alarm to inform users and a monitoring company if the tamper button is triggered
- Lock to secure the siren to SmartBracket
- Durable enclosure with IP54 and IK08 protection rating
- Jamming detection
- Frequency hopping to prevent radio interference
- Connection loss detection




Adjustable alerts

- Adjustable¹ alarm volume: from 85 dB to 107 dB
- Adjustable alarm duration: from 3 s to 3 min
- Selectable sound patterns
- Group mode for the siren to respond to events and security mode changes in its assigned group only



System supervision

- Low battery notifications and status display in Ajax apps
- Automatic device self-diagnosis with state report generation
- Notifications in case of malfunctions



Easy installation and setup

- Adding to the system via a QR code
- SmartBracket mounting panel for installation without enclosure disassembly
- Bubble level to check the inclination angle of the mounting during installation
- Remote control and configuration in mobile and desktop Ajax apps
- Installation kit with all necessary fasteners
- Up to 10 years of operation on enhanced pre-installed batteries
- Possibility to connect an external 12 V $\overline{=}$ power supply

Compliance with standards EN 50131 (Grade 3) Compatibility with hubs and range extenders For detailed information, scan the QR code or follow the link:  ajax.systems/tools/devices-compatibility/?models=SSP.G3.J	Communication with a hub or range extender Superior Jeweller communication technology Frequency bands 865.0–868.0 MHz 868.0–868.6 MHz 868.7–869.2 MHz 869.4–869.65 MHz Each device supports these four bands Communication range² up to 3,500 m up to 11,450 ft In open space	Alerts Alarm Audible, LED Entry/exit delay Audible, LED Security mode Audible, LED Security state LED Chime feature Audible If the feature is enabled, the siren will make a short beep to indicate that opening detectors have been triggered while the system was disarmed. After-alarm indication LED	Features Alarm volume from 85 dB to 107 dB at a distance of 1 m (3.3 ft) away from the siren Adjusted by a PRO or a user with admin rights in Ajax apps Alarm duration from 3 s to 3 min Siren sound frequency 1,400–1,600 Hz
Power supply Batteries 8 × CR123A (pre-installed) Battery life (TBC) up to 10 years Backup optional external 12 V[⎓] power supply	Installation Operating temperature range from −25 °C to +60 °C from −13 °F to +140 °F Operating humidity up to 95%	Enclosure Color white, black Dimensions 210 × 210 × 71 mm 8.27" × 8.27" × 2.80" Weight 1,146 g 40 oz Protection class IP54 IK08	Complete set Superior StreetSiren Plus G3 Jeweller 8 × CR123A battery (pre-installed) Installation kit Quick start guide

¹ Measured at a distance of 1 m (3.3 ft) away from the siren.

² Communication range depends on a hub model. More information: ajax.systems/hub-compare/



For detailed information, scan the QR code or follow the link:
<https://ajax.systems/support/devices/superior-streetsiren-plus-g3-jeweller/>

-  support@ajax.systems
-  @AjaxSystemsSupport_Bot
-  ajax.systems