

4MP outdoor IP dome

- IP Dome 4MP@25ips, Smart H.265+
- ICR, 0.003 lux, Smart IR 30m
- 2.8mm fixed lens
- WDR 120dB, 3D-NR, 4 ROI
- Human detection
- RJ45, Onvif, IP67, 3AXIS, PoE.

**Reference / Model**

IPC-T4EN / IPC-T4EN

4 megapixel 1/2.9" CMOS sensor

Video compression: Smart H.265+, Smart H.264+, H.265, H.264, MJPEG

Resolution: 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)

Stream 1: 4MP (1~25 ips)

Stream 2: D1 (1~25 fps)

Day/night mode with removable mechanical filter

Smart IR: 1 led, 30 meters

0.03 lux F2.0 (color), 0.003 lux F2.0 (B/W), 0 lux IR On

2.8 mm fixed lens

Angle of view: 92°(H), 50°(V), 107°(D)

Image modes: BLC, HLC, WDR 120dB, 3D-NR, Mirror.

White balance with 6 modes

4MP outdoor IP dome

Reference / Model	IPC-T4EN / IPC-T4EN
Automatic and manual gain control	
Supports 4-zone motion detection, 4 regions of interest (ROI) and 4-zone privacy masking	
Human detection and classification	
Network interface: RJ45 (10/100 Base-T)	
Network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP, P2P	
ONVIF (Profile S/T), CGI, SDK and API support	
Up to 6 users	
Remote viewing via IE, Chrome, Firefox browsers	
Management software	
Compatible with IOS and Android mobile devices	
Power supply: 12V DC / PoE (802.3af)	
Consumption: 3.5W (12V) / 4.3W (PoE)	
Storage temperature of -40°C ~ +60°C	
Operating temperature: -40°C ~ +60°C (-40°C ~ +60°C)	
Relative humidity: <95%.	
IP67 degree of protection	
Plastic housing	
Dimensions: Ø109 (H) x 85,5 mm	
Net weight: 250 g	
Gross weight: 380 g	
3AXIS: 0°~360°(PAN), 0°~78°(TILT), 0°~360°(Rotation)	