

DS-2CE56D0T-IT3E 2 MP PoC Fixed Turret Camera



- 2 MP PoC turret camera
- EXIR 2.0: advanced infrared technology with 40 m IR distance
- Water and dust resistant (IP67)
- Transmits both HD video and power over the same coaxial cable

▪ Specification

Camera	
Image Sensor	2.0 megapixel progressive scan CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
Focal Length & FOV	2.8 mm, horizontal FOV: 103.55° 3.6 mm, horizontal FOV: 82.63° 6 mm, horizontal FOV: 54.38° 8 mm, horizontal FOV: 37.96° 12 mm, horizontal FOV: 24.36°
Lens Mount	M12
Illuminator	
Supplement Light Range	Up to 30 m
Image	
Image Settings	Brightness, Mirror, Sharpness, AGC
Frame Rate	PAL: 1080P@25fps NTSC: 1080P@30fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	DWDR, BLC
Noise Reduction	2D DNR
Supplement Detection(PIR)	
PIR Range	Up to 40 m
Interface	
Video Output	1 HD analog output
General	
Power	12 VDC ±30%/PoC.af, max. 4 W
Material	Plastic
Dimension	110 mm × 93.2 mm (4.33" × 3.67")
Weight	Approx. 350 g (0.77 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67






▪ Available Model

DS-2CE56D0T-IT3E(12mm)

- DS-2CE56D0T-IT3E(8mm)
- DS-2CE56D0T-IT3E(6mm)
- DS-2CE56D0T-IT3E(3.6mm)
- DS-2CE56D0T-IT3E(2.8mm)

▪ **Accessory**

▪ **Optional**

<p>DS-1280ZJ-S Junction Box</p>	<p>DS-1276ZJ-SUS Corner Mount</p>	<p>DS-1275ZJ-SUS Vertical Pole Mount</p>	<p>DS-1280ZJ-TR13</p>	<p>DS-1281ZJ-S Inclined Ceiling Mount</p>
				
<p>DS-1272ZJ-110-TRS Wall Mount</p> 