





# Join the pro squad with the 24" G-Master Red Eagle, built for pure speed with a 240Hz refresh rate.

Gain the competitive edge you need to unlock your full gaming potential with the 24" GB2471HSU monitor with FHD (1920x1080) resolution. Featuring an ultra-fast 0.3ms MPRT and a 240Hz refresh rate, this monitor ensures smooth gameplay. Compatible with NVIDIA G-SYNC so you can make split second decisions and forget about ghosting effects or smearing issues. The ability to adjust brightness and the dark shades with the Black Tuner delivers greater viewing performance in shadowed areas and the IPS panel technology guarantees superb image quality.

Available also with fixed stand : G-Master G2471HS-B1



Fast IPS

The lightning-fast IPS panel with Full HD 1920x1080 resolution delivers ultra-smooth gameplay and vibrant, true-to-life colours with exceptional accuracy and wide viewing angles.



240Hz

With 240Hz refresh rate the force is with you! Make split second decisions and be sure the image on the screen is always sharp and smooth.



Diagonal	23.8", 60.5cm
Panel	Fast IPS
Native resolution	1920 x 1080 @240Hz (2.1 megapixel full HD, DisplayPort)
Aspect ratio	16:9
Panel brightness	350 cd/m <sup>2</sup>
Static contrast	1000:1
Advanced contrast	80M:1
Response time (MPRT)	0.3ms
Viewing zone	horizontal/vertical: horizontal°/vertical 178°, right/left: 0°/0°, up/down: 0°/0°
Colour support	16.7mln 8bit
Horizontal Sync	30 - 285kHz
Viewable area W x H	527 x 296.5mm, 20,7 x 11,7"
Pixel pitch	0.275mm
Colour	matte, black



### INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.0, max. 1920 x 1080 @240Hz) DisplayPort x1 (v.1.2, max. 1920 x 1080 @240Hz)
USB HUB	x2 (1x Type A v.3.2 Gen 1 (5Gbps, 4.5W), 1x Type C (5Gbps, 5W)
HDCP	yes
Headphone connector	yes



**FEATURES** 

Flicker free yes
Adaptive Sync support G-SYNC - 1920 x 1080 @48-240Hz, DisplayPort Only
<b>Extra</b> i-Style Colour
HDR Yes, HDR10 Ready
OSD languages EN, DE, FR, IT, PT, RU, JP, CZ, NL, PL
Speakers 2 x 2W
<b>Convenience</b> Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX



#### **MECHANICAL**

Display position adjustments	height, pivot (rotation), swivel, tilt
Height adjustment	150mm
Rotation (PIVOT function)	90°
Swivel stand	90°; 45° left; 45° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes



Cables

#### ACCESSORIES INCLUDED



### POWER MANAGEMENT

Power supply unit	internal
Power supply	AC AC - 100V, 240 /V, 50Hz
Power usage	18W typical, 0.5W stand by, 0.3W off mode



## SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	E
,	
REACH SVHC	above 0.1%: Lead



#### **DIMENSIONS / WEIGHT**

Product dimensions W x H x D	540 x 378.5 (498.5) x 171mm
Box dimensions W x H x D	650 x 140 x 420mm
Weight (without box)	4.8kg
Weight (without stand)	3.1kg
Weight (with box)	7.1kg
EAN code	4948570126354

