



Bullet 2

Model: IPC-F22FEP/IPC-F22FEN

1080P H.265 Bullet Wi-Fi Camera

Bullet 2 delivers 2MP live monitoring with a choice of 2.8mm/3.6mm/6mm lens option, it supports four night vision modes for clear-as day clarity even in pitch dark. With IP67 certified, the camera can be used outdoors under different weather conditions. With built-in spotlight and 110dB security siren, Bullet 2 actively keeps unwelcome visitors away from what you care about.





Human Detection

Quickly find human targets in you home



Smart Color Night Vision

Support four-mode night vision for clear-as day clarity even in pitch dark



Active Deterrence

Scare away unwelcome visitors with built-in spotlight and 110dB security siren



IP67

Weatherproof from dust and water



Two-way Talk

Real-time communicate with people at the camera



Diversified Storage

Supports NVR, Cloud Storage or Micro SD card (up to 256GB)



Alarm Notification

Sends instant motion-activated alerts to your mobile phone



Wi-Fi Connection

IEEE802.11b/g/n(2.4GHz)



Stay close with what you care

With Cloud service, you will have access to what you care as long as Internet is available. You can record daily or motion videos on Cloud and play back anytime anywhere.





Specifications

Camera

1/2.8" 2 Megapixel Progressive CMOS 2MP(1920 x 1080)

Night Vision: 30m(98ft) Distance 2.8mm/3.6mm/6mm Fixed Lens

Field of View: 2.8mm; 108° (H), 56° (V), 128° (D)

3.6mm: 88° (H), 46° (V), 104° (D) 6mm: 54° (H), 29° (V), 63° (D)

Video & Audio

Video Compression : H.265/H.264 Up to 25/30 fps Frame Rate 16x Digital Zoom

Built-in Mic & Speaker, 110dB Siren

Built-in Spotlight

Notice Management

Motion Detection Configurable Region Human Detection

What's in the box

- 1x Camera
- 1x Quick Start Guide
- 1x Power Adapter

Network

1 x 100Mbps Ethernet Port Wi-Fi:IEEE802.11b/g/n, Dual Antenna Imou App: iOS, Android ONVIF

Auxiliary Interface

Micro SD Card Slot (up to 256GB) Reset Button

General

DC 12V1A Power Supply Power Consumption:<5.32W Material: Plastic and Metal

Working Environment:-30° C~+60° C, Less Than 95%RH Dimensions: $147.7 \times 74.2 \times 74.2 \text{mm}$ (5.8 × 2.9 × 2.9inch)

Weight: 357g (0.8 lb)

CE, FCC, IP67

- 1x Screw Package
- 1x Installation Position Map
- 1x Waterproof Connector

