

## KeyPad Outdoor Jeweller

Wireless keypad supporting authentication via Pass, Tag, smartphones, and codes. For outdoor and indoor use.

## <sup>-</sup> Contactless authorization

- Pass cards and Tag key fobs supporting DESFire® technology
- Smartphones with Bluetooth via BLE technology
- Remote configuration of access control devices
- Protection against authentication via unauthorized access devices





**IK08** 

## \*\*\*- Management with codes

- Four types of codes: for registered users, for unregistered users, a keypad code, and an RRU code
- Keypad locking when someone tries to guess the code
- Duress code: if a user is forced to disarm the facility
- Remote management: codes can be created, changed, or removed in Ajax apps

## Sabotage resistance

- Tamper alarm: the enclosure is hardwired with two tamper buttons
- IK08 enclosure impact protection
- Device authentication to prevent spoofing
- Holding screw to secure the device on SmartBracket
- Panic button in case of emergencies

### Jeweller

communication technology

- Up to 1,700 m (5,550 ft) of radio communication between the keypad and a hub or range extender in an open space
- Data is encrypted throughout the transmission process
- Regular polling to display current device states
- Frequency hopping to prevent radio interference and jamming

# Additional features

Big mechanical buttons with a resilient press mechanism for easy and fast access, even in gloves

Automation devices control along with security mode change

A built-in buzzer to inform about alarms, security mode changing, Chime, etc.

Authorization confirmation: arming/disarming using access control devices requires confirmation with a code

Bypass mode: initiated at entry/exit delay in case of changing security mode to confirm arming/disarming via the main keypad

Up to 3 years of battery life with automatic low battery notifications

### Quick installation and setup

- IP66 enclosure for outdoor and indoor use
- Installation without disassembling the enclosure
- Built-in bubble level for a perfectly accurate mounting position

- Pairing with a hub via QR code
- Remote control and configuration via Ajax apps
- All the necessary fasteners included in the installation kit

#### Compliance with standards

EN 50131 (Grade 2) PD 6662:2017

### Compatibility

For detailed information, scan the QR code or follow the link:



ajax.systems/tools/devicescompatibility/?models=KP.O.J

### Communication with a control panel

Jeweller communication technology

Frequency bands 866.0-866.5 MHz 868.0-868.6 MHz 868.7-869.2 MHz 905.0-926.5 MHz 915.85-926.5 MHz

921.0-922.0 MHz

Depends on the sales region

**Communication range** up to 1,700 m up to 5,550 ft

Polling interval 12-300 s

In an open space

Adjusted by a PRO or user with admin rights in Ajax apps

#### **Features**

Contactless access Pass cards and Tag key fobs (up to 200 devices)

Support for BLE (up to 200 smartphones)

Access codes up to 200 personal codes for registered users up to 99 codes for unregistered users 1 keypad code

**Duress code** up to 200 personal duress codes 1 keypad duress code

Panic button

#### Installation

Operating temperature range from -25 °C to +60 °C

**Operating humidity** up to 80%

from -13 °F to 140 °F

**Protection class** IP66 (in progress)

Impact protection IK08 (in progress)

#### Power supply

Battery 2 × CR123A battery (pre-installed)

Battery life up to 3 years

Optional external power supply 10.5-14 V = , up to 1 A

#### **Enclosure**

Color white, graphite, black

**Dimensions**  $170 \times 45 \times 31,5 \text{ mm}$  $6.69" \times 1.77" \times 1.24"$ 


Weight 258 g 9.1 oz

Tamper alarm

#### Complete set

KeyPad Outdoor Jeweller SmartBracket mounting panel Installation kit Quick start guide

















For detailed information, scan the QR code or follow the link: