

DHI-LM86-S400 Dahua 86 inch LED Monitor



Series Overview

The Dahua Ultra Series Oversized Monitor is designed with an industrial LCD panel, delivering UHD resolution for vibrant and clear visuals. Available in 75", 86", and 98" sizes, it offers a range of rich video interfaces. This series is extensively used in conference rooms, monitoring rooms, exhibition halls, retail stores, and various indoor display scenes.

Technical Specification

Display	
Model	DHI-LM86-S400
LCD Technology	IPS
Backlight	DLED
Screen Size	86 inch
Aspect Ratio	16:9
Viewing Angle	178° (H) / 178° (V)
Display Mode	Horizontal, vertical
Resolution	3840 (H) × 2160 (V)
Refresh Rate	60 Hz
Display Color	10 bit
Brightness	350 cd/m² (max)
Contrast Ratio	1,100:1
Response Time	8 ms
Lifespan	30,000 hrs
Surface Treatment	Haze 28%, 2H

- 4K Ultra-HD resolution
- Anti-glare panel, suitable for continuous 24/7 operation
- 178°/178° extra-wide viewing angle for overall viewing performance
- High fidelity digital processing for a brilliant and vivid video
- 8ms response time for no motion blur, judder or ghosting
- Support HDMI, DP, VGA and other signal input
- Built-in speaker
- Infrared remote control



Device Ports

Speaker	10 W × 2
Input Port	DP × 1, HDMI × 2, VGA × 1, USB × 1, audio × 1, RS-232 in \times 1
Output Port	RS232 out × 1

Power & Environmental Conditions


Power Supply	100~240 VAC (±10%), 50/60 Hz	
Power Type	Built-in Power	
Power Consumption	170 W (basic), 320 W (typ.), 360 W (max)	
Standby Power Consumption	<0.5 W	
Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)	
Operating Humidity	10%-80% (RH)	
Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)	
Storage Humidity	5%–90% (RH)	
General		
Product Dimensions	1,952.8 mm × 1,123.4 mm × 78.9 mm (76.88" × 44.23" × 3.11") (W × H × D), without wall-mount bracket	
Package Size	2,100 mm × 1,270 mm × 225 mm (82.68" × 50" × 8.86") (W × H × D)	
Frame Width	U/L/R/D:27.2 mm/27.2 mm/27.2 mm/27.2 mm	
Net Weight	46.5 kg (102.52 lb)	
Gross Weight	66 kg (145.51 lb)	
Wall Mount VESA	800 mm × 400 mm (31.50"×15.75")	
orage Humidity eneral roduct Dimensions ackage Size ame Width et Weight ross Weight	5%–90% (RH) 1,952.8 mm × 1,123.4 mm × 78.9 mm (76.88" × 44.23" 3.11") (W × H × D), without wall-mount bracket 2,100 mm × 1,270 mm × 225 mm (82.68" × 50" × 8.86") (W × H × D) U/L/R/D:27.2 mm/27.2 mm/27.2 mm/27.2 mm 46.5 kg (102.52 lb) 66 kg (145.51 lb)	


Ultra Series | DHI-LM86-S400

Accessory	Power cord, wall-mount bracket, HDMI cable, remote control, user's manual, legal and regulatory information etc.
Certification	
Certifications	CE EMC, CE LVD, CE ERP

Ordering Information				
Туре	Model	Description		
LED Monitor	DHI-LM86-S400	Dahua 86 inch LED Monitor		

Dimensions (mm[inch])





Rev 002.000 © 2024 Dahua. All rights reserved. Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.