

DH-PFS3005-5ET-L

5-Port Desktop Fast Ethernet Switch



- Compact design: Miniature size and light weight make it easy to deploy
- Plug and play: No configuration required
- Green technology: Adopts high quality environmentally friendly plastics
- 7×24H: Stable performance for long-term operation

System Overview

5 × 10/100 Mbps adaptive ports, highly integrated design, compact, portable, easy to operate, suitable for small and medium office and home networks.

Technical Specification

Performance

Layer	Layer 2
Managed	No

Hardware

Standard Power Supply	Yes
PoE	No
Ethernet Port	5
Ethernet Port Rate	100 Mbps
Power Supply	5V/500mA DC
Operating Temperature	-10°C to 55°C (14°F to 131°F)
Operating Humidity	10%–90%
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Storage Humidity	10%–90%
Power Consumption	Idling: 0.65W Full load: 1.3W

Performance

Switching Capacity	1 Gbps
Packet Forwarding Rate	0.744 Mpps
Packet Buffer Memory	448 Kbits
MAC Table Size	1K
Standards Compliance	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE802.3az

Application

The product is applicable to small and medium office and home networks.

General

ESD	Air discharge: 8kV Contact discharge: 4kV
Thunderproof	Common mode: 2kV
Net Weight	0.04 kg (0.09 lb)
Gross Weight	0.14 kg (0.31 lb)
Dimensions	77 mm × 46 mm × 21 mm (3.03" × 1.81" × 0.83")
Packaging Dimensions	94 mm × 55 mm × 107 mm (3.70" × 2.17" × 4.21")

Dimensions (mm[inch])

