

**INFORMATION**

## 98" 4K UHD Most powerful professional digital signage display with advanced control and connectivity options

The ProLite LE9864UHS-B1AG is a 98" 4K UHD digital signage powerhouse designed to elevate your business's visual communication. With Android 14 OS, [iiSignage<sup>2</sup>](#) (CMS), [iiControl](#) (DMS), and [iiShare](#) (Wireless Presentation), managing content is effortless. It's WiFi enabled for remote content delivery and offers reliable 24/7 operation. Perfect for retail, corporate, hospitality, or restaurant settings, this display ensures a captivating audience experience with its versatile design and high brightness.




## Android OS

Thanks to Android OS, you can easily customize the display to your needs by installing applications directly to it.

## 4 SIMPLE STEPS

TO REACH YOUR AUDIENCE



## iiSignage<sup>2</sup>

iiSignage<sup>2</sup> is our digital signage content management platform to easily show and control your content and to manage your displays in a secure way. The Content Management System (CMS) gives you total control of your messaging and advertising remotely and safely.



## Signal FailOver

FailOver is a feature which automatically detects input sources. When there is no signal on the default input it will automatically switch to the next available input. FailOver allows customers to prioritize a number of inputs (incl. Browser, Media Player and Custom) and ensures your content is always actively displayed, assuring active content at all times.

## SPECIFICATION

### 01 DISPLAY CHARACTERISTICS

|   |   |
|---|---|
| <b>Design</b>                           | Thin bezel  |
| <b>Diagonal</b>                         | 98", 247.7cm  |
| <b>Panel</b>                            | VA, Anti-Glare coated glass, matte finish, haze 25%                   |
| <b>Native resolution</b>                | 3840 x 2160 @60Hz (8.3 MegaPixels 4K UHD)                             |
| <b>Aspect ratio</b>                     | 16:9  |
| <b>Panel brightness</b>                 | 500 cd/m <sup>2</sup>   |
| <b>Static contrast</b>                  | 5000:1  |
| <b>Response time (GTG)</b>              | 6.5ms   |
| <b>Viewing zone</b>                     | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| <b>Colour support</b>                   | 1.07G (8 Bits+FRC)  |
| <b>Horizontal Sync</b>                  | 57 - 62kHz  |
| <b>Viewable area W x H</b>              | 2158.8 x 1214.4mm, 85 x 47.8"   |
| <b>Bezel width (sides, top, bottom)</b> | 21.5mm, 21.8mm, 21.8mm  |
| <b>Pixel pitch</b>                      | 0.487mm   |
| <b>Bezel colour and finish</b>          | black, matte  |

### 02 INTERFACES / CONNECTORS / CONTROLS

|                               |  |
|-------------------------------|--|
| <b>Digital signal input</b>   | HDMI x2 (v.2.0, max. 3840x2160 @60Hz)<br>USB-C x1 (DP Alt, 15W PD)             |
| <b>Monitor control input</b>  | RS-232c x1 (2.5mm sub-mini jack)<br>RJ45 (LAN) x1<br>IR x1 (3.5mm stereo mini) |
| <b>Audio output</b>           | Mini jack x1 (3.5mm)<br>Speakers 2 x 10W                                       |
| <b>Monitor control output</b> | RS-232c x1 (2.5mm)<br>IR loop through x1 (3.5mm)                               |
| <b>HDCP</b>                   | v.1.4 & 2.0  |
| <b>USB ports</b>              | x2 (v.2.0)   |

### 03 FEATURES

|                                     |   |
|-------------------------------------|---|
| <b>Integrated software</b>          | Android 14 OS, iiSignage <sup>2</sup> , iiControl, iiShare, EShare, FailOver, TeamViewer, PDF & Media Player, iiBrowser, File manager |
| <b>WiFi</b>                         | yes (Built-in, 2.4G/ 5G)  |
| <b>Hardware</b>                     | CPU: A73*4, GPU: G52 MC1, RAM: 4GB, ROM: 32GB   |
| <b>Extra</b>                        | Wall mounting kit included (VESA 700x500mm)   |
| <b>Max. non-stop operating time</b> | 24/7  |
| <b>Anti image retention</b>         | yes   |
| <b>Media playback</b>               | yes   |

|                        |       |
|------------------------|-------|
| <b>Housing (bezel)</b> | metal |
|------------------------|-------|

## 04 GENERAL

|                        |   |
|------------------------|---|
| <b>OSD languages</b>   | EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL, SV, FI, DA, NB  |
| <b>Control buttons</b> | Power Indicator, Power button, Remote Sensor  |
| <b>User controls</b>   | network (status, Wifi, ethernet, hotspot), picture (brightness, contrast, sharpness, black level, tint, colour, noise reduction, gamma selection, colour temp., colour control, picture reset), audio (balance, treble, bass, volume, audio out, max. volume, min. volume, mute, audio out sync, speaker setting, audio reset), OSD setting (OSD timeout, OSD H-Position, OSD V-position, OSD transparency, information OSD), general (logo and animation, wallpaper, no signal image, schedule, off timer), screen (zoom mode, custom zoom, system rotation, screen reset), device (power on status, RS232 routing, IR control, power saving, panel saving, monitor info, other), channel (boot on source, rename input channel, auto source switching, signal lost detection, HDMI version), system (language, system update, setting reset, factory reset, Android setting), admin (menu lock, meeting room, HDMI CEC, screen share, Miracast standby, log export) |
| <b>Plug&amp;Play</b>   | DDC2B   |

## 05 MECHANICAL

|                                    |                                    |
|------------------------------------|------------------------------------|
| <b>Orientation</b>                 | landscape                          |
| <b>Fanless design</b>              | yes                                |
| <b>VESA mounting</b>               | 700 x 500mm                        |
| <b>Operation temperature range</b> | 0°C - 40°C                         |
| <b>Storage temperature range</b>   | - 20°C - 60°C                      |
| <b>MTBF</b>                        | 50.000 hours (excluding backlight) |

## 06 ACCESSORIES INCLUDED

|                       |   |
|-----------------------|---|
| <b>Cables</b>         | power, HDMI, RS-232c  |
| <b>Guides</b>         | quick start guide, safety guide   |
| <b>Other</b>          | Wall mount bracket, Wall mount guide, Screws, Screw anchors, Stickers for screw holes |
| <b>Remote control</b> | yes (batteries included)  |

## 07 POWER MANAGEMENT

|                          |  |
|--------------------------|--|
| <b>Power supply unit</b> | internal                                   |
| <b>Power supply</b>      | AC 100 - 240V, 50/60Hz                     |
| <b>Power usage</b>       | 388W typical, 0.5W stand by, 0.3W off mode |

## 08 SUSTAINABILITY

|  |   |
|--|---|
| <b>Regulations</b>   | CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH (UKCA, RoHS2.0, PFOS) |
| <b>Energy efficiency class (Regulation (EU) 2017/1369)</b> | G   |

09 DIMENSIONS / WEIGHT

**Product dimensions** 2202 x 1257.7 x 110.5mm  
W x H x D

**Box dimensions W x** 2390 x 1500 x 280mm  
**H x D**

**Weight (without box)** 61kg

**Weight (with box)** 77.9kg

**EAN code** 4948570125227



POWER HDMI RS-232C

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IYAMA CORPORATION. ALL RIGHTS RESERVED