

INFORMATION**27" QHD IPS monitor with 4-side slim bezel and EPEAT Silver certification**

The ProLite X2797QSU is perfect if you want a compact, high-performance display that fits seamlessly into a multi-monitor setup. The four-side slim bezel creates a clean, modern workspace and ensures uninterrupted visuals across screens.



With a sharp QHD 2560x1440 resolution and IPS panel technology, this 27-inch monitor delivers outstanding image clarity, consistent colour accuracy and wide viewing angles. It is ideal for professionals who multitask, work with detailed visuals or compare documents side by side. Whether you're working on documents, editing content or browsing the web, flicker-free technology and TÜV Rheinland Eye Comfort certification ensure the display meets strict criteria for low blue light and long-term viewing safety.

It features integrated stereo speakers, a four-port USB hub, and versatile connectivity options including HDMI, DisplayPort and a headphone socket, keeping your workspace organised and efficient.

Certified to EPEAT Silver and TCO10 standards, the X2797QSU offers reliable performance and essential user-focused features for productive modern work environments.



Expand your view with QHD

QHD 2560x1440 resolution offers up to 77% more screen space than Full HD, giving you plenty of room to multitask efficiently, view more content at once, and work with greater precision, without constantly switching between windows.



Multi-screen setup for a panoramic workspace

Connect multiple ultra-slim bezel monitors to create a panoramic workspace, keep your apps in view, streamline multitasking, and boost productivity.



Feel the difference with certified eye comfort

Flicker-free technology, blue light reduction, and true-to-life colour accuracy combine to reduce eye strain and support lasting visual comfort. Backed by TÜV Rheinland Eye Comfort certification, this display gives you peace of mind while working, browsing, or creating for hours with greater ease and clarity.



Versatile connectivity for all your devices

Connect multiple devices and accessories in one simple step with HDMI, DisplayPort and the USB hub, streamlining your workspace for maximum efficiency and ensuring a tidy, uninterrupted workflow.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

| | |
|-----------------------------|--|
| Design | 4-side slim bezel |
| Diagonal | 27", 68.5cm |
| Panel | IPS Panel Technology LED, matte finish |
| Native resolution | 2560 x 1440 @75Hz (3.7 megapixel QHD) |
| Aspect ratio | 16:9 |
| Panel brightness | 350 cd/m ² |
| Static contrast | 1000:1 |
| Advanced contrast | 80M:1 |
| Response time (MPRT) | 1ms |
| Viewing zone | horizontal/vertical: 178°/ 178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support | 16.7mln |
| Horizontal Sync | 30 - 112kHz |
| Viewable area W x H | 596.7 x 335.7mm, 23.5 x 13.2" |
| Pixel pitch | 0.233mm |
| Colour | matte, black (black) |

02 INTERFACES / CONNECTORS / CONTROLS

| | |
|----------------------------|---|
| Signal input | HDMI x2 (v.1.4) DisplayPort x1 (v.1.2) |
| USB HUB | x4 ((2x Type-A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type-C (5Gbps, 5W)) |
| HDCP | yes |
| Headphone connector | yes |

03 FEATURES

| | |
|------------------------------|---|
| Blue light reducer | yes |
| Flicker free | yes |
| Adaptive Sync support | yes |
| Extra | i-Style colour, Eye Comfort |
| OSD languages | EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA |
| Control buttons | Joystick: Centre: Power/Menu, Up / Signal Select, Down, Left / Shortcut, Right / Volume |
| User controls | picture adjust (brightness, contrast, ECO, ACR, OD, motion blur reduction, Adaptive Sync), colour settings (i-Style colour, RGB range, colour temperature, user preset), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, extra1 (sharpness, video mode adjust, opening logo, power LED), Extra2 (shortcut key, FW version), input select, audio settings (volume, mute audio), reset (reset all) |
| Speakers | 2 x 2W |
| Convenience | Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX |

04 MECHANICAL

| | |
|-------------------------------------|-----------------|
| Display position adjustments | tilt |
| Tilt angle | 20° up; 5° down |
| VESA mounting | 100 x 100mm |
| Cable management system | yes |

05 ACCESSORIES INCLUDED

| | |
|---------------|--|
| Cables | power (1.8m), USB (1.5m), HDMI (1.5m), DP (1.8m) |
| Other | quick start guide, safety guide |

06 POWER MANAGEMENT

| | |
|--------------------------|---|
| Power supply unit | internal |
| Power supply | AC 100 - 240V, 50/60Hz |
| Power usage | 16W default, 0.5W stand by, 0.3W off mode |

07 SUSTAINABILITY

| | |
|--|---|
| Regulations | TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA |
| Energy efficiency class (Regulation (EU) 2017/1369) | D |
| EPEAT Silver | *registration varies by country, go to www.epeat.net for details |
| REACH SVHC | above 0.1%: Lead |
| Warranty | 5 years (for details and eligible countries please check the Warranty section of our website) |

08 DIMENSIONS / WEIGHT

| | |
|---|---------------------|
| Product dimensions W x H x D | 613 x 428.5 x 190mm |
| Box dimensions W x H x D | 688 x 442 x 126mm |
| Weight (without box) | 4.0kg |
| Weight (with box) | 6.3kg |
| EAN code | 4948570126880 |



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED