

UT-15 Series Universal Transmitter

Providing Flexibility and Agility for Security Deployment



UT-15 Series is a universal contact-monitoring transmitter, designed to monitor an activation of a specific wired sensor which is connected to it. Whenever the wired device is triggered, UT-15 Series will transmit an alarm signal to Control Panel and further notify users of an alarm event. It provides flexibility and agility in the security deployment.

UT-15 Series design consists of a cover and base. The cover contains all electronics and the base provides a means for fixing the device. An enclosed tamper switch provides tamper protection against unauthorized device opening and/or removal.

Features

- Detect an activation of a connected wired device, including Door Contact, Passive Infrared Motion Detector, Smoke Detector or Panic Button
- Compact & slim design for easy mounting
- Low Battery detection
- Randomized Supervision signals for trouble-free system integrity checking
- Tamper protection protects against unauthorized removal, sabotage or unsteady installation

Specifications

UT-15SL-F1

Frequency	433 MHz / 868 MHz / 869 MHz
Power Source	3V, CR2 Lithium battery x 1
Battery Life	6.4 years*
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	107 mm x 32 mm x 22 mm

UT-15

Frequency Available	433 MHz / 868 MHz
Power Source	Lithium 1/2 AA batteries x 1 (pre-inserted)
Battery Life	2.8 years*
Operating Temperature	-10°C to 50°C (14°F to 122°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	107 mm x 32 mm x 22 mm

* Note: The actual battery life may vary with product settings, usage patterns and operating environment.

UT-15 Series Universal Transmitter

Ordering Information

UT-15SL-F1	Universal Transmitter with long battery life
UT-15	Universal Transmitter