

VTNC1003C-D 2-wire Controller



• Supports slide rail installation.

• In a 2-wire hybrid system, the 2-wire controller isolates the power supply and the signal to reduce the absorption of signals by the power supply of the input terminal during transmission.

E\CH

Technical Specification

Performance

Installation

renormance	
Casing Material	PC + ABS
General	
Appearance Color	White
Power Supply	48 V, 0.9 A
Certifications	CE
Product Dimensions	74.9 mm × 46.7 mm × 28.7 mm (2.95" × 1.84" × 1.13") (L × W × H)
Operating Temperature	-10 °C to +55 °C (14 °F to +131 °F)
Operating Humidity	10%–95% (RH)
Operating Altitude	0 m-3,000 m (0 ft-9,842.51 ft)
Power Consumption	3.5 W
Gross Weight	0.31 kg (0.68 lb)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Humidity	≤95% (RH), non-condensing

Ordering Information Model Туре Description VTNC1003C-D VTNC 2-wire Controller

Application



Dimensions (mm [inch])

ΠB 5 2







EΒ

© 2024 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product. Rev 002.000