

**INFORMATION****Eco-conscious 24" IPS monitor for modern workplaces**

The ProLite X2493HSU is the ideal choice if you are looking for a compact, high-performance display that integrates effortlessly into a multi-monitor workspace. Its four-side ultra-slim bezel design creates a clean, modern aesthetic and delivers seamless visuals across multiple screens.



The IPS panel ensures sharp detail, accurate colour reproduction and wide viewing angles, while the 120Hz refresh rate provides a smooth and responsive user experience. Whether you are working on documents, editing content or browsing the web, flicker-free technology and a blue light reducer help reduce eye strain and improve long-term viewing comfort.

For convenience and efficiency, the X2493HSU features built-in speakers, a two-port USB hub, HDMI and DisplayPort inputs, and a headphone socket. This simplifies your desk setup and provides flexible connectivity for your devices.

With EPEAT registration, TCO10 Certified compliance and an Energy Label C rating, this monitor supports your sustainability objectives without compromising on performance.



### Multi-screen setup for a panoramic workspace

Connect multiple ultra-slim bezel monitors to create a panoramic workspace, keep your apps in view, streamline multitasking, and boost productivity.



### Versatile connectivity for all your devices

Connect multiple devices and accessories in one simple step with HDMI, DisplayPort and the USB hub, streamlining your workspace for maximum efficiency and ensuring a tidy, uninterrupted workflow.



### Built-in audio without extra clutter

Enjoy clear, pleasant sound for calls, videos, and music while keeping your desk free of extra speakers, thanks to the integrated audio.



### Reduced eye strain & fatigue

Work, study or play longer without eye fatigue, thanks to flicker-free technology and reduced blue light emissions. These features help minimize eye strain and improve visual comfort, allowing you to stay focused and productive throughout the day.

## SPECIFICATION

### 01 DISPLAY CHARACTERISTICS

<b>Design</b>	4-side slim bezel
<b>Diagonal</b>	23.8", 60.5cm
<b>Panel</b>	IPS panel technology LED, matte finish
<b>Native resolution</b>	1920 x 1080 @120Hz (2.1 megapixel Full HD)
<b>Aspect ratio</b>	16:9
<b>Panel brightness</b>	350 cd/m <sup>2</sup>
<b>Static contrast</b>	1500:1
<b>Advanced contrast</b>	80M:1
<b>Response time (MPRT)</b>	1ms
<b>Viewing zone</b>	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
<b>Colour support</b>	16.7mIn (sRGB: 96%; NTSC: 72%)
<b>Horizontal Sync</b>	30 - 140kHz
<b>Viewable area W x H</b>	527 x 296.5mm, 20.7 x 11.7"
<b>Pixel pitch</b>	0.275mm
<b>Colour</b>	matte, black

### 02 INTERFACES / CONNECTORS / CONTROLS

<b>Signal input</b>	HDMI x1 (v.1.4) DisplayPort x1 (v.1.2)
<b>USB HUB</b>	x2 (v. 2.0 (DC5V, 500mA))
<b>HDCP</b>	yes
<b>Headphone connector</b>	yes

### 03 FEATURES

<b>Blue light reducer</b>	yes
<b>Flicker free</b>	yes
<b>Adaptive Sync support</b>	HDMI/DP 1920x1080 @120Hz
<b>Extra</b>	i-Style colour
<b>OSD languages</b>	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
<b>Control buttons</b>	Joystick: Centre: Power/Menu, Up/Signal Select, Down, Left/Submenu, Right/Volume
<b>User controls</b>	picture adjust (brightness, contrast, ECO, ACR, OD, motion blur reduction, Adaptive Sync), colour settings (i-Style colour, blue light reducer, RGB range, colour temperature, user preset), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, extra1 (sharpness, video mode adjust, opening logo, power LED), extra 2 (shortcut key, FW version), input select, audio settings (volume, mute audio), reset (reset all)
<b>Speakers</b>	2 x 2W
<b>Convenience</b>	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

## 04 MECHANICAL

<b>Display position adjustments</b>	tilt
<b>Tilt angle</b>	20° up; 3° down
<b>VESA mounting</b>	100 x 100mm
<b>Cable management system</b>	yes

## 05 ACCESSORIES INCLUDED

<b>Cables</b>	power (1.8m), USB (1.5m), HDMI (1.5m)
<b>Other</b>	quick start guide, safety guide

## 06 POWER MANAGEMENT

<b>Power supply unit</b>	internal
<b>Power supply</b>	AC 100 - 249V, 50/60Hz
<b>Power usage</b>	12W default, 0.5W stand by, 0.3W off mode

## 07 SUSTAINABILITY

<b>Regulations</b>	TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
<b>Energy efficiency class (Regulation (EU) 2017/1369)</b>	C
<b>EPEAT Silver</b>	*registration varies by country, go to <a href="http://www.epeat.net">www.epeat.net</a> for details
<b>REACH SVHC</b>	above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

<b>Product dimensions W x H x D</b>	539 x 387 x 175mm
<b>Box dimensions W x H x D</b>	615 x 395 x 126mm
<b>Weight (without box)</b>	3.3kg
<b>Weight (with box)</b>	5.1kg
<b>EAN code</b>	4948570126606





All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IYAMA CORPORATION. ALL RIGHTS RESERVED